


MSRP: \$2,999 Color: SHIVER WHITE

SPECIFICATIONS

SUGGESTED USE	Casual Pavement Adventure
SIZE	Small, Medium, Large
TOTAL WEIGHT	Small: 52.2 lb., Medium: 52.4 lb., Large: 52.6 lb
FRAME	Yamaha hydroformed aluminum. Integrated battery. Water bottle boss. Tapered headtube. Internal shift/brake hose routing. Rack/fender compatible.
FORK	SR Suntour NEX-E25. 63mm travel. 12x100mm Thru-Axle
BATTERY	Yamaha Lithium Ion 500 Wh, 36V, 13.4Ah
DRIVE UNIT	Yamaha PWSeries ST, 3-bolt mount, Display A
CRANKARM	Square taper spindle, Length: (S) 165mm, (M,L) 170mm
CHAINRING	SAMOX® 44T
SHIFTER	SHIMANO® M2010, 9-speed
REAR DERAILLEUR	SHIMANO® M3100 SGS
BRAKES/ROTORS	Hydraulic front/rear
ROTORS	Centerlock 180mm (front), 160mm (rear)
CASSETTE	SHIMANO® HG400 9-speed, 11-13-15-17-20-23-26-30-36T
CHAIN	KMC® e11, 118 links
HUBS	Front: 12x100mm Quick-Release Thru-Axle (QRTA) Rear: 12x142mm QRTA with integrated speed sensor
RIMS	27.5" 32-hole dual channel welded pin with eyeleted spoke
HOLES	24.5mm external width, 19mm internal width
SPOKES	14g SUS30 with brass nipple
TIRES/TUBES	CST C1996 27.5x2.0"
HEADSET	Integrated bearing with 30mm of spacers
STEM	31.8mm clamp diameter, 6° rise, 80mm
HANDLEBAR	31.8mm diameter, 640mm width
GRIPS/TAPE	Two-tone ergonomic locking
SEATPOST	30.9mm diameter, length: (S) 295mm, (M/L) 345mm
SEATPOST COLLAR	Alloy 2-bolt, 35mm diameter
SADDLE	Yamaha Urban Comfort Cro-Mo Rail
ACCESSORIES	Included Kickstand, Yamaha battery charger, Bell, LED Headlight

LIMITED WARRANTY

3-year limited warranty* on frame, drive unit, and battery; 1-year limited warranty* on other components (Yamaha supports original-equipment component manufacturers' warranties).

FEATURES

Fitness specific ergonomics and geometry

Wheels and tires ready for durability and acceleration

Ergonomic grips for comfort and functionality

Fender and rear rack compatible

Quad Sensor System with rear hub speed sensor

Rated power: 250 W (nominal), 500 W (max)

Max torque: 70Nm

Max speed support: 28 mph

5 Assist modes: AUTO, ECO+, ECO, STANDARD, HIGH

Walk Assist Feature

FRAME GEOMETRY

TOP TUBE (mm)	539	569	599
REACH LENGTH (mm)	355	370	390
STACK HEIGHT (mm)	603	614	626
HEAD TUBE LENGTH (mm)	120	130	140
HEAD TUBE ANGLE	69.8°	70.5°	71.1°
SEAT TUBE ANGLE	73.1°	72°	71.6°
STANDOVER HEIGHT (mm)	777	814	847
HANDLEBAR WIDTH (mm)	640	640	640
CRANK ARM LENGTH (mm)	165	170	170
SEAT POST LENGTH (mm)	295	345	345
STEM LENGTH (mm)	80	80	80
BB DROP (mm)	63	63	63
REAR CENTER (mm)	465	465	465
WHEELBASE (mm)	1061	1071	1090
SEAT TUBE LENGTH (mm)	430	490	552

*Go to www.yamahabicycles.com/warranty-overview/ for more information.


MSRP: \$2,999 Color: PAINTED DESERT

SPECIFICATIONS

SUGGESTED USE	Casual Pavement Adventure
SIZE	Small, Medium, Large
TOTAL WEIGHT	Small: 52.2 lb., Medium: 52.4 lb., Large: 52.6 lb
FRAME	Yamaha hydroformed aluminum. Integrated battery. Water bottle boss. Tapered headtube. Internal shift/brake hose routing. Rack/fender compatible.
FORK	SR Suntour NEX-E25. 63mm travel. 12x100mm Thru-Axle
BATTERY	Yamaha Lithium Ion 500 Wh, 36V, 13.4Ah
DRIVE UNIT	Yamaha PWSeries ST, 3-bolt mount, Display A
CRANKARM	Square taper spindle, Length: (S) 165mm, (M,L) 170mm
CHAINRING	SAMOX® 44T
SHIFTER	SHIMANO® M2010, 9-speed
REAR DERAILLEUR	SHIMANO® M3100 SGS
BRAKES/ROTORS	Hydraulic front/rear
ROTORS	Centerlock 180mm (front), 160mm (rear)
CASSETTE	SHIMANO® HG400 9-speed, 11-13-15-17-20-23-26-30-36T
CHAIN	KMC® e11, 118 links
HUBS	Front: 12x100mm Quick-Release Thru-Axle (QRTA) Rear: 12x142mm QRTA with integrated speed sensor
RIMS	27.5" 32-hole dual channel welded pin with eyeleted spoke
HOLES	24.5mm external width, 19mm internal width
SPOKES	14g SUS30 with brass nipple
TIRES/TUBES	CST C1996 27.5x2.0"
HEADSET	Integrated bearing with 30mm of spacers
STEM	31.8mm clamp diameter, 6° rise, 80mm
HANDLEBAR	31.8mm diameter, 640mm width
GRIPS/TAPE	Two-tone ergonomic locking
SEATPOST	30.9mm diameter, length: (S) 295mm, (M/L) 345mm
SEATPOST COLLAR	Alloy 2-bolt, 35mm diameter
SADDLE	Yamaha Urban Comfort Cro-Mo Rail
ACCESSORIES	Included Kickstand, Yamaha battery charger, Bell, LED Headlight

LIMITED WARRANTY

3-year limited warranty* on frame, drive unit, and battery; 1-year limited warranty* on other components (Yamaha supports original-equipment component manufacturers' warranties).

FEATURES

Fitness specific ergonomics and geometry

Wheels and tires ready for durability and acceleration

Ergonomic grips for comfort and functionality

Fender and rear rack compatible

Quad Sensor System with rear hub speed sensor

Rated power: 250 W (nominal), 500 W (max)

Max torque: 70Nm

Max speed support: 28 mph

5 Assist modes: AUTO, ECO+, ECO, STANDARD, HIGH

Walk Assist Feature

FRAME GEOMETRY

TOP TUBE (mm)	539	569	599
REACH LENGTH (mm)	355	370	390
STACK HEIGHT (mm)	603	614	626
HEAD TUBE LENGTH (mm)	120	130	140
HEAD TUBE ANGLE	69.8°	70.5°	71.1°
SEAT TUBE ANGLE	73.1°	72°	71.6°
STANDOVER HEIGHT (mm)	777	814	847
HANDLEBAR WIDTH (mm)	640	640	640
CRANK ARM LENGTH (mm)	165	170	170
SEAT POST LENGTH (mm)	295	345	345
STEM LENGTH (mm)	80	80	80
BB DROP (mm)	63	63	63
REAR CENTER (mm)	465	465	465
WHEELBASE (mm)	1061	1071	1090
SEAT TUBE LENGTH (mm)	430	490	552

*Go to www.yamahabicycles.com/warranty-overview/ for more information.


MSRP: \$2,999 Color: URBAN SAGE

SPECIFICATIONS

SUGGESTED USE	Casual Pavement Adventure
SIZE	Small, Medium, Large
TOTAL WEIGHT	Small: 52.2 lb., Medium: 52.4 lb., Large: 52.6 lb
FRAME	Yamaha hydroformed aluminum. Integrated battery. Water bottle boss. Tapered headtube. Internal shift/brake hose routing. Rack/fender compatible.
FORK	SR Suntour NEX-E25. 63mm travel. 12x100mm Thru-Axle
BATTERY	Yamaha Lithium Ion 500 Wh, 36V, 13.4Ah
DRIVE UNIT	Yamaha PWSeries ST, 3-bolt mount, Display A
CRANKARM	Square taper spindle, Length: (S) 165mm, (M,L) 170mm
CHAINRING	SAMOX® 44T
SHIFTER	SHIMANO® M2010, 9-speed
REAR DERAILLEUR	SHIMANO® M3100 SGS
BRAKES/ROTORS	Hydraulic front/rear
ROTORS	Centerlock 180mm (front), 160mm (rear)
CASSETTE	SHIMANO® HG400 9-speed, 11-13-15-17-20-23-26-30-36T
CHAIN	KMC® e11, 118 links
HUBS	Front: 12x100mm Quick-Release Thru-Axle (QRTA) Rear: 12x142mm QRTA with integrated speed sensor
RIMS	27.5" 32-hole dual channel welded pin with eyeleted spoke
HOLES	24.5mm external width, 19mm internal width
SPOKES	14g SUS30 with brass nipple
TIRES/TUBES	CST C1996 27.5x2.0"
HEADSET	Integrated bearing with 30mm of spacers
STEM	31.8mm clamp diameter, 6° rise, 80mm
HANDLEBAR	31.8mm diameter, 640mm width
GRIPS/TAPE	Two-tone ergonomic locking
SEATPOST	30.9mm diameter, length: (S) 295mm, (M/L) 345mm
SEATPOST COLLAR	Alloy 2-bolt, 35mm diameter
SADDLE	Yamaha Urban Comfort Cro-Mo Rail
ACCESSORIES	Included Kickstand, Yamaha battery charger, Bell, LED Headlight

LIMITED WARRANTY

3-year limited warranty* on frame, drive unit, and battery; 1-year limited warranty* on other components (Yamaha supports original-equipment component manufacturers' warranties).

FEATURES

Fitness specific ergonomics and geometry

Wheels and tires ready for durability and acceleration

Ergonomic grips for comfort and functionality

Fender and rear rack compatible

Quad Sensor System with rear hub speed sensor

Rated power: 250 W (nominal), 500 W (max)

Max torque: 70Nm

Max speed support: 28 mph

5 Assist modes: AUTO, ECO+, ECO, STANDARD, HIGH

Walk Assist Feature

FRAME GEOMETRY

TOP TUBE (mm)	539	569	599
REACH LENGTH (mm)	355	370	390
STACK HEIGHT (mm)	603	614	626
HEAD TUBE LENGTH (mm)	120	130	140
HEAD TUBE ANGLE	69.8°	70.5°	71.1°
SEAT TUBE ANGLE	73.1°	72°	71.6°
STANDOVER HEIGHT (mm)	777	814	847
HANDLEBAR WIDTH (mm)	640	640	640
CRANK ARM LENGTH (mm)	165	170	170
SEAT POST LENGTH (mm)	295	345	345
STEM LENGTH (mm)	80	80	80
BB DROP (mm)	63	63	63
REAR CENTER (mm)	465	465	465
WHEELBASE (mm)	1061	1071	1090
SEAT TUBE LENGTH (mm)	430	490	552

*Go to www.yamahabicycles.com/warranty-overview/ for more information.